



079700 Royal Enfield Himalayan Hugger Fitting Instructions

Kit includes:

2X	Cable Tie (430 X 7.6mm)	CAB0430A
2X	Circular Rubber Foot	CRUB0003
1X	Rubber Strip (60mm approx)	CRUB0010

This hugger requires no modifications to the bike when fitting. A single cable tie is required for installation, the second cable tie is supplied as a spare. The design retains the original chainguard.

- With the motorcycle on its centre stand (or paddock stand) remove the rear wheel. Split the chain by removing the spring clip, using a pair of long nosed pliers. When removing this split link, take note of the four small 'O' rings and ensure that they are correctly installed during reassembly.
- Once the rear wheel has been removed, clean the area around the head of the swinging arm. Fit the cable tie to the hugger as shown in Fig 1. Now slide the hugger onto the head of the swinging arm in order to achieve a close fit. Guide the open end of the cable tie down the front of the head of the swinging arm and pass it through the lower slot on the hugger.
- Join the two halves of the cable tie together on the inside of the hugger and pull strongly with both hands to achieve a tight fit - see Fig 2.
- Ensure that the hugger is now fully seated into the face of the head of the swinging arm.
- The rear wheel can now be refitted. Ensure that the chain adjusters on the left and right legs of the swinging arm are of equal length and that there is 15-20mm of slack in the chain.
- Ensure that the spring clip for the rear chain link is reinstalled in the correct direction - see Fig 3.

Fig 1



Fig 2



Fig 3



Any questions?
sales@pyramid-plastics.co.uk
01427 677990
www.pyramid-plastics.co.uk

Follow us on social media and feel free to leave us a review!

